Hemisphere

Crescent® V100 Series GPS Compass Affordable Heading and Positioning Smart Antenna









Experience superior navigation from the accurate heading and positioning performance available with the Crescent V100 Series GPS Compass. The rugged enclosure combines Hemisphere GPS' Crescent Vector board and two multipath-resistant antennas for portability and simple installation. The half-meter length smart antenna mounts easily to a flat surface or pole. The stability and maintenance-free design of the Crescent V100 replaces traditional gyrocompasses at a fraction of the cost.

23



Powered by **Cres(ent**

The latest Hemisphere GPS products are powered by Crescent Receiver Technology, the future of precision GPS.

Key Crescent V100 Series Advantages

- Affordable solution delivers 2D GPS heading accuracy better than 0.5 degree rms
- Differential positioning accuracy of less than 60 cm, 95% of the time
- Smart antenna design ensures simple installation and portability
- Integrated gyro and tilt sensor deliver fast start-up times and provide heading updates during temporary loss of GPS
- Fast heading and positioning output rates up to 20 Hz
- Differential options including SBAS (WAAS, EGNOS, etc.) and optional beacon differential
- COAST[™] technology maintains accurate solutions for 40 minutes or more after loss of differential signal

Hemisphere

Crescent® V100 Series GPS Compass

GPS Sensor Specifications

Receiver Type:	L1, C/A code, with carrier phase smoothing	
Channels:	Two 12-channel, parallel tracking	
	(Two 10-channel when tracking SBAS)	
Update Rate:	Standard 10 Hz, optional 20 Hz (position	
	and heading)	

Horizontal Accuracy:

< 0.6 m 95% confidence (DGPS)* < 2.5 m 95% confidence (autonomous, no SA)**

Heading Accuracy:< 0.5° rms</th>Pitch / Roll Accuracy:< 1 ° rms</td>Rate of Turn:90° / s maxStart up Time:< 60 s typical</td>Heading Fix:< 20 s</td>Satellite Reacquisition:< 1 s</td>

Beacon Sensor Specifications (V110 version)

2-channel, parallel tracking
283.5 to 325 kHz
Automatic (signal strength or range)
and manual
IEC 61108-4 beacon standard

Communications

Serial ports: 2 full duplex RS-232 and 1 half-duplex RS-422

Baud Rates: 4800 - 57600

Correction I/O Protocol: RTCM SC-104, L-Dif (Hemisphere GPS proprietary)

Data I/O Protocol: NMEA 0183, Crescent binary, L-Dif (Hemisphere GPS proprietary)

Heading Warning I/O: Open relay system indicates invalid heading

Environmental

Operating Temperature: Storage Temperature: Humidity: -30°C to +70°C (-22°F to +158°F) -40°C to +85°C (-40°F to +185°F) 100% non-condensing

Power

Input Voltage:	9 to 36 V
Power Consumption:	< 4 W
Current Consumption:	< 360 m/
Isolation:	Power su

9 to 36 VDC < 4 W < 360 mA @ 12 VDC Power supply isolated from serial ports

Reverse Polarity Protection: Yes

Mechanical

 Dimensions

 (not including mounts):
 60 cm L x 16 cm W x 18 cm H

 (23.6" L x 6.3" W x 7.1" H)

 Weight:
 1.5 kg (3.3 lb)

 Power/Data Connector:
 18-pin, Environmentally sealed

Aiding Devices

Gyro: Single axis gyro provides reliable <1° heading for periods up to 3 minutes when loss of GPS lock has occurred

Tilt Sensor: Assists in fast start up of RTK solution

- Depends on multipath environment, number of satellites in view, satellite geometry, baseline length (for local services), and ionospheric activity
- ** Depends on multipath environment, number of satellites in view, and satellite geometry

© Copyright November 2006, Hemisphere GPS LLC. All rights reserved. Specifications subject to change without notice. Hemisphere GPS and the Hemisphere GPS logo and Crescent and the Crescent logo are trademarks of Hemisphere GPS LLC. Made in Canada. Warranty: Each Hemisphere GPS product is covered by a limited one-year warranty on parts and labor.

HEMISPHERE GPS LLC Corporate Headquarters 4110 - 9th Street S.E. Calgary, AB T2G 3C4 Canada Phone: 403.259.3311 Fax: 403.259.8866 Toll Free: 800.274.9190 info@hemispheregps.com www.hemipheregps.com